


### Specification

Nominal Voltage	12V		
Nominal Capacity(10hrs rate)	20.0AH		
Dimension	Length	181.5 ± 1mm(7.14inches)	
	Width	77 ± 1mm(3.03inches)	
	Container Height	167.5 ± 1mm(6.59 inches)	
	Total Height (with Terminal)	167.5 ± 1mm(6.59 inches)	
Approx Weight	Approx 5.78 Kg (12.74 lbs)		
Design Float Life	12 years at 25°C(77°F)		
Container Material	ABS		
Rated Capacity	20.0AH/1.00A	(20hr, 1.80V/cell, 25°C/77°F)	
	18.6AH/1.86A	(10hr, 1.80V/cell, 25°C/77°F)	
	17.0AH/3.40A	( 5hr, 1.75V/cell, 25°C/77°F)	
	15.3AH/5.10A	( 3hr, 1.75V/cell, 25°C/77°F)	
	12.56AH/12.56A	( 1hr, 1.60V/cell, 25°C/77°F)	
Max. Discharge Current	300A (5s)		
Internal Resistance	Approx 15mΩ		
	Discharge :	-15~50°C (5~120°F)	
	Charge :	0~40°C (5~104°F)	
Operating Temp.Range	Storage : -15~40°C (5~104°F)		
	Nominal Operating Temp. Range 25 ± 3°C (77 ± 5°F)		
Cycle Use	Initial Charging Current less than 6.0A.Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C		
	Standby Use No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C		
Capacity affected by Temperature	40°C (104°F)	103%	
	25°C ( 77°F)	100%	
	0°C ( 32°F)	86%	
Self Discharge	≤1.5% per month		
	RUZET LPA series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required.		



■ Terminal  
Unit: mm [inches]



### Applications

- UPS and EPS
- Emergency light
- Railway signal and aircraft signal system
- Marine and power stations Alarm and security system
- Electronic apparatus and equipment
- Communication power supply, DC power supply

### Constant Current Discharge (Amperes) at 25°C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	38.1	29.2	24.2	20.9	16.2	11.9	10.1	5.95	4.65	3.78	3.09	2.68	2.16	1.80	0.99
1.80V/cell	51.1	37.4	29.3	24.8	19.1	13.9	11.3	6.49	5.01	4.04	3.31	2.87	2.29	1.86	1.00
1.75V/cell	57.6	41.1	32.0	26.6	19.8	14.4	11.8	6.73	5.10	4.13	3.40	2.95	2.33	1.91	1.01
1.70V/cell	63.5	44.8	34.1	28.0	20.7	15.0	12.2	6.90	5.24	4.24	3.49	3.01	2.36	1.95	1.03
1.65V/cell	70.0	48.3	36.3	29.7	21.8	15.4	12.4	7.00	5.47	4.39	3.58	3.08	2.40	1.99	1.04
1.60V/cell	77.2	52.4	38.8	31.7	23.0	16.0	12.6	7.30	5.63	4.52	3.70	3.14	2.42	2.01	1.05

### Constant Power Discharge (Watts) at 25°C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	69.6	54.0	45.2	39.5	30.9	22.9	19.4	11.6	9.07	7.40	6.05	5.26	4.26	3.57	1.96
1.80V/cell	92.5	68.2	53.9	46.0	35.9	26.5	21.6	12.5	9.71	7.86	6.46	5.62	4.51	3.68	1.98
1.75V/cell	102.0	73.8	58.1	49.0	36.9	27.2	22.5	12.9	9.85	8.00	6.61	5.76	4.58	3.77	2.00
1.70V/cell	109.3	78.6	61.2	51.1	38.2	28.2	23.1	13.2	10.1	8.20	6.77	5.87	4.64	3.84	2.03
1.65V/cell	118.8	84.0	64.6	53.9	40.0	28.6	23.5	13.3	10.5	8.45	6.93	5.98	4.70	3.91	2.05
1.60V/cell	128.0	89.1	67.9	56.8	41.9	29.7	23.6	13.9	10.8	8.69	7.13	6.09	4.73	3.95	2.06